



5T LINEAR CABLE TENSIONER

Equipment Specification Sheet

- 5T CAPACITY
- CABLE DIAMETER UP TO 350mm
- WEIGHT 3.5T
- REMOTELY OPERATED
- INCLUDING HPU

FEATURES

- 5 Wheel pairs, 10 Hydraulic motors with individual gear boxes and hydraulic brakes.
- 3 Operating modes: Manual via potential meter, constant speed and constant tension.
- Operations via remote control console c/w local and remote emergency stop.
- Wheel pairs can be opened, closed, started and stopped either simultaneously or separately.
- Tension measurement optional





TECHNICAL DETAILS

- **Dimensions** 4.6m L x 1.6m W x 1.3m H
Weight 3.5T
- **Wheel pairs** 5x wheel pair – wheel dia 620mm
Wheel drive 10x hydraulic motors with individual gear boxes and brakes
- **Required power** 440V, 60Hz, 75kW
Speed control 0 – 50m/min (0 – 3,000m/h)

- **Working pressure** 280bar
- **Cable opening** min. 0mm / max. 350mm
- **HPU dimensions** 2.8m L x 1.1m W x 2.2m H
HPU Weight 2.8T
- **Controls** Remotely operated

5T LINEAR CABLE TENSIONER



Dutch Offshore Contractors BV
 4382 NM, Vlissingen
 The Netherlands

www.dutchoffshorecontractors.com
info@dutchcontractors.com
 T +31 (0)85 273 63 10